

Specification

Series 782 Cable Reel

Cable Reel shall be Series 782 manufactured by Nederman. The cable reel shall include 14 Gauge SJO Cord suitable for 115V at 10 Amps. This Cord shall be supplied in a length of 40 ft. and shall have a single industrial receptacle. The cable reel shall have built in thermal overload protection with manual re-set. The cable reel shall be constructed of a high impact plastic body and drum.

The reel shall have an integral metal swivel bracket that allows the reel to pivot freely through 160°. The reel shall be design for installation on the wall or ceiling. The ratchet mechanism shall retain cable in the withdrawn position; pulling cable past the ratchet latch shall permit automatic cable rewind. A totally encased spring drive shall be constructed of reverse wound spring steel and be factory adjusted for each specific cable. A high strength plastic sealed spring cover shall protect the spring and swivel enclosures.

The Cable Reel shall have cable outlet slot that allows free movement of the cable through a range of 32°. This slot shall reduce cable wear by allowing a full range of movement that provides the most suitable outlet angle. An adjustable cable stop collar shall be supplied made of High Density Polyethylene.

All components shall be corrosion resistant.

The cable reel shall meet ISO 9001 Quality Standard, and ISO 14001 Environmental Standard.

The cable reel shall have a standard 2-year warranty.