

Specification

Triangular Exhaust Nozzle 803 Series

The 803 series vehicle exhaust extraction nozzle shall be the type supplied by Nederman, Inc. It shall be constructed of heavy duty EPDM rubber which shall reduce surface heat build up on the nozzle and protect the vehicle from scrapes or paint damage.

The nozzle shall be secured to the vehicle by a fully adjustable, quick release locking clamp which will ensure positive attachment to vehicle exhaust pipe. A built in guard screen shall prevent debris from being drawn into the exhaust system. The nozzle shall have a flexible metal heat shield hose attached which slides into the exhaust hose, thereby acting as a heat shield to the exhaust hose. The exhaust nozzle shall be equipped with two ports: one will enable sampling of exhaust gases while attached to the exhaust pipe and the other port will allow the return of the sample gas into the exhaust system. The nozzle mouth shall have an triangular opening which will accommodate single exhaust pipes and most twin side by side exhaust pipes. The nozzle shall resist temperatures of up to 175° F continuously and up to 325° F intermittently.

The Triangular Exhaust Nozzle, Series 803, warranty shall be for a period of one year from date of shipment from Nederman, Inc.

Nozzle Model No.	Diameter Hose	Weight
20803461	3"	6.6 lbs.
20803561	4"	7.7 lbs.
20803661	5"	7.5 lbs.