

# Specification

## Series 893 Hose Reel - Air/Water/Oil/Grease/Fluids

Series 893 Open Hose Reel manufactured by Nederman suitable for low or high pressure applications. Unit available without hose or with hose: ½", 3/8", or ¼" I.D. delivery hose 33' - 50' in length rated from 220 to 5100 psi as specified, with 3' supply hose and guide ring. Standard industrial or food grade hoses available or as specified. The Service Reel housing, constructed of steel, is available in galvanized or stainless steel including a rotating mounting frame of tubular steel to facilitate wall/ceiling/or bench mount installation.

The safety ratchet latch retains the hose in the withdrawn position. Pulling the hose just past the ratchet latch releases the hose for automatic rewind. The adjustable hose stop tapered design permits smooth recoil action. Hose outlet rollers guide the hose upon unwinding or rewinding to reduce friction and hose wear. The hose outlet can be positioned to the desired hose outlet angle.

A totally enclosed spring (spring steel) is factory adjusted for the mounted hose. Spring tension can be adjusted externally as needed. The swivel is constructed with an external brass shaft and an internal large bore stainless steel swivel shaft to provide fast flow. Service or changing hose can be safely performed without dismantling the reel. Threaded connectors standard for all high pressure reels, clamp connection for low pressure reels or as specified.

All components shall be corrosion resistant.

### OPTIONAL ACCESSORIES:

150° Pivoting wall bracket, galvanized or stainless steel.

Waterguns, water lances, airguns, or other options as specified.

WARRANTY: one year. ISO 9001 Certified Quality System