

## Curtains



Standard sized curtains (see below) provided with 50 mm welded seam all around and with snap-fasteners on both sides for joining to obtain total desired width. Supplied with reinforced holes in the upper edge and steel suspension rings. All standard curtains are made of pliable self extinguishing PVC-material with flash point 320-390°C (600–730°F). Width: 1400 mm (55 in.), Thickness: 0.40-0.50 mm (0.016–0.020 in.). The Nederman yellow and clear transparent curtains are used for glare, splatter, grinding, dust etc. but are not aimed for welding, unlike our EN1598 compliant curtains that are ideal for welding applications.

### Replacement parts

Description	Part no.
PVC rings, 7-pack	60344976
Steel rings, 7-pack	60064850

Colour	Height, mm	Approvals	Part no.
Dark green (black), Opaque	1800	EN 1598	60313124
Dark green (black), Opaque	2400	EN 1598	60313125
Dark green (black), Opaque	2800	EN 1598	60313126
Dark green, Transparent	1800	EN 1598	60313424
Dark green, Transparent	2400	EN 1598	60313425
Dark green, Transparent	2800	EN 1598	60313426
Red / orange, Transparent	1800	EN 1598	60313324
Red / orange, Transparent	2400	EN 1598	60313325
Red / orange, Transparent	2800	EN 1598	60313326
Bronze, Transparent	1800	EN 1598	60313224
Bronze, Transparent	2400	EN 1598	60313225
Bronze, Transparent	2800	EN 1598	60313226
Yellow, Transparent	1800	-	60313524
Yellow, Transparent	2400	-	60313525
Yellow, Transparent	2800	-	60313526
Clear, Transparent	1800	-	60313624
Clear, Transparent	2400	-	60313625
Clear, Transparent	2800	-	60313626

*Steel suspension rings included. PVC-rings available as accessories. Total width of curtains shall be 10% longer than total required screening length to compensate for folding.*

## Curtain Screen



The protection curtain screens are easily movable for welding, grinding, turning, milling etc, and are ideal for the screening of temporary or permanent work places. The frame is manufactured from galvanised tube and the curtain of self-extinguishing PVC material (as the standard curtains above) and complying with EN1598 for welding. Delivered complete with frame and curtain with total dimension WxH=1700x2000 mm (67x79 in.) (just curtain H=1700 mm (67 in.)). Weight 7.5 kg (16 lbs).

Colour	Approvals	Part no.
Dark green (black) Opaque	EN 1598	60931052
Dark green Transparent	EN 1598	60931050
Red / orange Transparent	EN 1598	60931056

*Product availability may differ by country*